

RUST OFF®



135

Extreme Lubricant for Overdriven Machinery

A higher quality lubricant in the correct application always reduces downtime. It is always more cost effective to use wear particle analysis to determine the present condition of important machinery, rather than waiting for a breakdown.

Characteristics

- ✚ **Corrosion Prevention** – 135 is excellent for controlling corrosion and rust protecting metal in short term storage situations.
- ✚ **Prevents Down Time** – 135's Viscosity uses capillary action to quickly penetrate between frozen parts softening and dissolving the corrosion bonding matrix allowing quick and easy disassembly.
- ✚ **Lubrication Properties** – 135 allows lubrication in areas where a normal lubricants can not reach, it penetrates deep into close fitting components lubricating and freeing the surfaces.
- ✚ **Water Displacing Fluid** – 135 has the ability to rapidly shift water from all surfaces and is very effective in allowing instant starts from wet when used on machinery.
- ✚ **Safety** – Mainlube 135 contains no silicon. Mainlube 135 will not harm paint work, vinyl, rubber, metals.

✓ **PENERTRATING LUBRICANT**

✓ **RAPIDLY RELEASES SEIZURE**

✓ **PREVENTS FURTHER CORROISON**

✓ **EFFECTIVE MULTI-PURPOSE WORK SHOP TOOL**

✓ **AVAILABLE IN BULK & AEROSOL 435**

Distributed By



"Quality First, Quality Always"

PHONE: +353 (1) 287 58 59

WEBSITE: www.ilsltd.com

ISO 9001 Quality Approved

APPLY BY: Spray, Dip, Brush, Soaking, Hand Sprayer & Aerosol as Mainlube 435

DESCRIPTION

Penetrating Lubricant. Rapidly releases seizure and prevents further corrosion. 135 is an effective multipurpose work-shop tool.

CHARACTERISTICS:

Corrosion Prevention

Mainlube 135 is excellent for controlling corrosion and rust protecting metal in short term storage situations. 135 Will suppress and remove rust, corrosion and finger print smudging from steel surfaces. 135 Can be used to protect tools, outboard motors, lawn mowers, locks, hinges, parts storage etc.

Prevents Down Time

135's Viscosity uses capillary action to quickly penetrate between frozen parts softening and dissolving the corrosion bonding matrix allowing quick and easy disassembly. As exhaust specialists, panel beaters, wheel alignment, auto wreckers etc have a fixed time for each job. 135 saves downtime.

Lubrication Properties

135's Capillary action allows lubrication in areas where a normal lubricants cannot reach, it penetrates deep into close fitting components lubricating and freeing the surfaces. This makes 135 an extremely useful service product for maintenance engineers caretakers, sports people, hobbyists, house wives etc. Mainlube 135's clear and non-staining lubricating film can be used for lubricating squeaky hinges, locks, latches, pulleys, sewing machines, lawn mowers, car doors etc.

Water Displacing Fluid

135 has the ability to rapidly shift water from all surfaces and is very effective in allowing instant starts from wet when used on machinery like:-Automobiles, jet skis, snow mobiles, motor bikes, lawn mowers, out boards etc. Use where DEF Australia specification water displacing PX112 fluid is required.

Safety

Mainlube 135 contains no silicon. Mainlube 135 will not harm, paint work, vinyl, rubber, metals.

Note

CAUTION FLAMMABLE

Water displacing fluids require a solvent to allow them to work. Keep away from flames and pilot lights. Do not use or store in open flame areas. Dangerous goods class and subsidiary risk **3.2.**

Available in Bulk as 135 and Aerosol as 435.



135

Apply by: spray, dip, brush, soaking, hand sprayer
and aerosol as Mainlube 435

SPECIFICATIONS:

TEST	ASTM TEST METHOD	TEST RESULT
------	------------------	-------------

Density @ 15°C kg/L	D-1298	0.843
---------------------	--------	-------

Viscosity, cSt:		
-----------------	--	--

@ 40 °C	D-445	4.47
---------	-------	------

Flash Point (COC), °C	D-92	49.1
-----------------------	------	------

Pour Point (COC), °C	D-97	-19
----------------------	------	-----

Boil Point (COC), °C	-	145°C
----------------------	---	-------

Fingerprint Suppressive Action	-	Yes
--------------------------------	---	-----

Penetrating Fluid	-	Yes
-------------------	---	-----

Rust Protection, Cast Iron Chips	-	Pass
----------------------------------	---	------

RH 100%, 72 hours @ 20°C		
--------------------------	--	--

Application Aerosol		Drip, Spray, Dip, Brush,
------------------------	--	--------------------------

Removal	-	Petroleum Solvent,
---------	---	--------------------

MAINLUBE SUPERIOR MAINTENANCE LUBRICANTS
PTY LIMITED

ACN 001-748-876 SYDNEY AUSTRALIA

DISTRIBUTED BY: